



# **RAPTICAL LTD**

The Computer Company

tel: 25-312139, 25-430202, 99-412448  
www.raptical.com

fax: 25-430232  
sales@raptical.com

Address: Shop G14, Anna Court 4, 2 Georgios A str., 4047, Potamos Yermasoyas, Limassol, Cyprus

## Web Cameras

### **PK-720G WEBCAM WITH MIC 16 MEGAPIXELS**

€ 19.60 +VAT

Still image:Up to 16 Megapixel, 4608x3456 (software interpolated)  
Image sensor:1/6"CMOS, 640x480 pixels  
Frame rate:30fps@160x120, @320x240, @640x480  
Lens:F=2.4, f=3.5 mm  
View angle:54 degrees  
Focus range:Automatic focus, 10 cm to infinity  
Exposure control:Automatic  
White balance:Automatic  
Microphone:Built-in  
Computer interface:USB 2.0



### **PK-770G WEBCAM WITH MIC 16 MEGAPIXELS**

€ 18.20 +VAT

Sensor Type Sixth CMOS 640 x 480 pixels  
Built-in microphone  
Mount Universal  
Interface USB 2.0  
Photography 0.3 megapixel, with the possibility of interpolation to 16 megapixel  
Videography 0.3 megapixel, with the possibility of interpolation to 16 megapixel  
Focus Auto, 10 cm to infinity  
White Balance Auto  
Exposure control Auto  
Frame rate Up to 30 frames per second  
Filter frequency flickering ambient light 50Hz, 60Hz or not  
Viewing Angle 54 gradusa  
Focus of the lens F = 2.4 mm, f = 3.0 mm  
Food From the USB-port  
The size of the webcam 5.1 x 2.3 x 5.9 cm  
Weight 0.084 / 0.181 kg  
Color Black Gray  
**System Requirements:**  
Windows XP / Vista / Windows 7 / Mac OS 10.4.8 or later



### **PK-930H 1080p FULL-HD WEBCAM**

€ 22.40 +VAT

Sensor : 1080p Full HD  
Lense : Anti-glare  
Cable length(M) : 1.5M  
Product Weight(g) : 63.5  
Product Size(mm) : 83\*53\*36  
1080P Full HD  
High Fidelity Microphone  
Anti-Glare Coating



## UA0100 USB WEBCAM WITH LED LIGHTING & HEADSET LOGILINK

€ 15.40 +VAT

The set includes a webcam with LED lighting and a modern headset. The Internet Webcam from LogiLink has a 300k CMOS sensor with maximum resolution of up to 640x480 (interpolated up to 8M pixels). The intelligent mounting system combines a tight fit, guaranteed to your notebook or PC monitor. The LED of the webcam are automatically controlled so the webcam can be used in low light conditions. This modern headset is ideal for Internet telephony, video conferencing, voice recognition and interactive gaming. It is ultra light and guarantees a comfortable fit.

### Webcam:

CMOS Image Sensor: 300K pixels,  
interpolated to 8M pixels  
Stylish and rugged metal housing for a secure footing  
Integrated light meter guarantees with  
6 LEDs automatically for correct lighting  
Practical clamp for attachment to the notebook

### Headset:

Over Head Headset  
Flexible microphone incl. Integrated volume control  
3.5 mm jack



## WCS-2030 LEVEL1

€ 168.00 +VAT

IP Network Camera, 54 Mbps, wireless version

LevelOne's WCS-2030 is a compact-sized and perfect network camera for home and office surveillance systems. This device is able to transmit optimal synchronized video and audio over the Internet thus provides the remote monitoring capabilities.

In order to provide flexible connection possibilities, WCS-2030 can access control data and transmit video streaming either through a 54Mbps wireless network or an Ethernet connection. Also, the camera is easy to install in network environment without worrying about complex network set-up procedures. Once installed the wizard can provide easy set-up procedure for camera use. With a built-in web server, WCS-2030 provides an easy user interface for remote access to receive video signals from anywhere anytime over the Internet with the Internet Explorer browser. DDNS is configured to allow this camera to use an easier naming format to remember rather than an IP address.

The WCS-2030 bundles with free software that allows the administrator to monitor up to 16 channels simultaneously. The embedded software can also simulate a camera zoom function to record ideal images up to 640 x 480 pixels. This software utility supports even more features such as automatic snapshot, record streaming video directly to hard disk, enable motion detection and send event notification via e-mail, making this network camera a ideal solution to building a digital network-monitoring environment.

### Features:

Installs wherever on the IEEE 802.11 b/g wireless LAN or  
wired 10/100 Mbps Ethernet is available  
Optimal synchronization of audio & video  
Supports 4x digital zoom  
MPEG-4 compression minimizes bandwidth requirement  
Supports UPnP for Easy set-up and installation  
Friendly GUI for easy configuration  
Supports Windows 98SE/ME/2000/XP  
Intelligent motion detection  
Adjustable network bandwidth  
Event-notification via E-mail

